MURR ELEKTRONIK
stay connected

## MOTOR SUPPRESSOR


Varistor, 3x400VAC/5,5kW


3× 400 V AC
VDR
Suppressors for other voltages, frequencies, and motor ratings available on request. Do not use RC motor suppressors with frequency inverters.
Ferrule ends, load side securely fixed

**Link to Product**

### Illustration






Product may differ from Image

### Commercial data

| | |
|---|---|
| ECLASS-6.0 | 27371013 |
| ECLASS-6.1 | 27371013 |
| ECLASS-7.0 | 27371013 |
| ECLASS-8.0 | 27371013 |
| ECLASS-9.0 | 27371013 |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-28

| | |
|---|---|
| ECLASS-10.1 | 27371013 |
| ECLASS-11.1 | 27371013 |
| ECLASS-12.0 | 27371013 |
| ETIM-5.0 | EC000197 |
| customs tariff number | 85363010 |
| GTIN | 4048879018951 |
| Packaging unit | 1 |
| **Compatibility \| Compatible with** | |
| Appropriate contactors | Moeller, Siemens, Speaker+Shoe |
| **Electrical data \| Supply** | |
| Power frequency | 10 ... 400 Hz |
| **Electrical data \| Input** | |
| Input voltage AC | 400 V |
| **Mechanical data \| Mounting data** | |
| Height | 75 mm |
| Width | 45 mm |
| Depth | 100 mm |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 60 °C |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-28