

MIRO GSM DI6 DO4R 24VDC

The product is discontinued. Last order date 12/22/2017.

[Link to Product](#)

Commercial data	
ECLASS-6.0	27242216
ECLASS-7.0	27242216
ECLASS-8.0	27242216
ECLASS-9.0	27242216
ETIM-5.0	EC000740
customs tariff number	85176200
GTIN	4048879321303
Packaging unit	1
Electrical data Input	
Input voltage DC min.	12 V
Input voltage DC max.	48 V
Input current	15 mA
Electrical data Output	
Switching voltage AC max.	250 V
Switching voltage DC max.	250 V
Switching current max.	10 A
Device protection	
Condition lifetime	load-dependent
Device protection Electrical	
Degree of protection (EN IEC 60529)	IP20
Electrical lifetime	30000000 Cycles
Device protection Mechanical	
Mechanical endurance	30000000 Cycles
Mechanical data Material data	
Material contact	Ag Ni 90/10
Mechanical data Mounting data	
Mounting method	screwed, geschnappt
Suitable for mounting type	mounting rail, (EN 60715)
Height	80 mm
Width	90 mm
Depth	59,5 mm
Environmental characteristics Climatic	
Operating temperature min.	-25 °C
Operating temperature max.	55 °C
Storage temperature min.	-40 °C
Storage temperature max.	85 °C
Connection type 7	
Connection type 1	Ant
Connection type 2	Input
Connection type 3	Input Digital
Connection type 4	Output
Connection type 5	Output
Connection type 6	Prog
Connection type 7	SIM

Family construction form	SMA
Gender	female
No. of poles	2
PIN 1	Signal
PIN 2	PE
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
Color contact carrier	green
No. of poles	10
PIN 1	+
PIN 2	+
PIN 3	-
PIN 4	-
PIN 5	1
PIN 6	2
PIN 7	3
PIN 8	4
PIN 9	5
PIN 10	6
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
Color contact carrier	green
No. of poles	6
PIN 1	1
PIN 2	2
PIN 3	3
PIN 4	4
PIN 5	5
PIN 6	6
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
Color contact carrier	green
No. of poles	12
PIN 1	1 14
PIN 2	1 12
PIN 3	1 11
PIN 4	2 24
PIN 5	2 22
PIN 6	2 21
PIN 7	3 34
PIN 8	3 32
PIN 9	3 31
PIN 10	4 44
PIN 11	4 42
PIN 12	4 41
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
Color contact carrier	green
No. of poles	4
PIN 1	1

PIN 2	2
PIN 3	3
PIN 4	4
Family construction form	D-Sub
Gender	female
Color contact carrier	black
No. of poles	9
Family construction form	SIM
Gender	male
No. of poles	6