MURR ELEKTRONIK
stay connected

**Article discontinued since March/2018**


Product discontinued


Compact design
with plug relays
8 plugged relays; each 1 NO/NC contact
24 V DC
Diode + LED

## Link to Product

### Illustration






Product may differ from Image

CE

### Commercial data

| | |
|---|---|
| ECLASS-6.0 | 27371001 |
| ECLASS-7.0 | 27371001 |
| ECLASS-8.0 | 27371001 |
| ECLASS-9.0 | 27371001 |
| ETIM-5.0 | EC001437 |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-28

| | |
|---|---|
| customs tariff number | 85437090 |
| GTIN | 4048879411332 |
| Packaging unit | 1 |
| **Electrical data \| Output** | |
| Utilization category AC-12 (EN IEC 60947-5-1) | 6 A @ 24, 6 A @ 110 V, 6 A @ 230 V |
| Utilization category AC-15 (EN IEC 60947-5-1) | 3 A @ 24 V, 3 A @ 110 V, 3 A @ 230 V |
| Utilization category DC-13 (EN IEC 60947-5-1) | 1 A @ 24 V, 0,2 A @ 110 V, 0,1 A @ 230 V |
| Switching voltage AC max. | 250 V |
| Switching voltage DC max. | 250 V |
| Switching current max. | 6 A |
| **Installation** | |
| Connection cross section max. | 4 mm² |
| **Installation \| Connection** | |
| Connection | Screw terminals SK |
| Connection information | mit einzeln ausgeführten -A2-Anschlüssen |
| **Device protection \| Electrical** | |
| Rated surge voltage | 4 kV |
| **Mechanical data \| Mounting data** | |
| Mounting method | geschnappt |
| Suitable for mounting type | mounting rail, (EN 60715) |
| Height | 86 mm |
| Width | 67,5 mm |
| Depth | 75 mm |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-28