

## **LUG S 8 FOR SIGNAL TRANSFER**


250V / 8 A


8-pole Screw plug-in terminals

## **Link to Product**

## Illustration







Product may differ from Image

| Commercial data       |               |  |
|-----------------------|---------------|--|
| ECLASS-6.0            | 27143424      |  |
| ECLASS-6.1            | 27260708      |  |
| ECLASS-7.0            | 27141152      |  |
| ECLASS-8.0            | 27141152      |  |
| ECLASS-9.0            | 27141152      |  |
| ECLASS-10.1           | 27141152      |  |
| ECLASS-11.1           | 27141152      |  |
| ECLASS-12.0           | 27141152      |  |
| ETIM-5.0              | EC001283      |  |
| customs tariff number | 85369010      |  |
| GTIN                  | 4048879026291 |  |
| Packaging unit        | 1             |  |

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-08



stay connected

| Electrical data   Supply                 |                           |
|--|---------------------------|
| Operating voltage AC                     | 250 V                     |
| Operating current max.                   | 8 A                       |
| Installation                             |                           |
| Connection cross-section solid max.      | 4 mm <sup>2</sup>         |
| Installation   Connection                |                           |
| Connection                               | Screw terminals SK        |
| Mechanical data   Mounting data          |                           |
| Mounting method                          | geschnappt                |
| Suitable for mounting type               | mounting rail, (EN 60715) |
| Height                                   | 75 mm                     |
| Width                                    | 45 mm                     |
| Depth                                    | 66 mm                     |
| Environmental characteristics   Climatic |                           |
| Operating temperature min.               | -20 °C                    |
| Operating temperature max.               | 60 °C                     |