

PROFIBUS-PLUG-MALE (SUB-D) 90° WITH PG

Cut clamp for rigid and flexible wires

Bus connection plug 90°  
PROFIBUS  
SUB-D9 (male), IDC terminals, rigid and flexible cable, programming device connection  
PROFIBUS, FC cable rigid/flexible, 1× 2× 0.64 mm², for outer diameter 8.0 ±0.5 mm

Link to Product

Illustration



Product may differ from Image



| Commercial data             |                         |
|-----------------------------|-------------------------|
| ECLASS-6.0                  | 27279221                |
| ECLASS-7.0                  | 27440104                |
| ECLASS-8.0                  | 27440104                |
| ECLASS-9.0                  | 27440102                |
| ECLASS-10.1                 | 27242692                |
| ECLASS-11.1                 | 27242692                |
| ECLASS-12.0                 | 27242692                |
| ETIM-5.0                    | EC001855                |
| customs tariff number       | 85389091                |
| GTIN                        | 4048879050555           |
| Packaging unit              | 1                       |
| Electrical data             |                         |
| Terminating resistor        | connectable, integrated |
| Electrical data   Supply    |                         |
| Operating voltage DC min.   | 4,75 V                  |
| Operating voltage DC max.   | 5,25 V                  |
| Current consumption max.    | 12,5 mA                 |
| Industrial communication    |                         |
| Data transmission rate max. | 12 MBit/s               |
| Installation   Connection   |                         |

Connection Cut clamps IDC

**Device protection | Electrical**

Degree of protection (EN IEC 60529) IP20

Pollution Degree 2

**Mechanical data | Mounting data**

Height 72 mm

Width 40 mm

Depth 17 mm

**Environmental characteristics | Climatic**

Operating temperature min. -25 °C

Operating temperature max. 60 °C

Storage temperature min. -25 °C

Storage temperature max. 80 °C