

CAN-PLUG-MALE (SUB-D) 90°

Screw terminals up to 1Mbps/s

Bus connection plug 90°
SUB-D9 (female), screw terminals
max. 1 Mbit/s with switchable terminal resistors
CANopen
Plastic housings with good resistance against chemicals and oils.
The resistance to aggressive media should be individually tested for your application. Further details on request.

Link to Product

Illustration



Product may differ from Image

| Commercial data | |
|-------------------------------------|-------------------------|
| ECLASS-6.0 | 27279221 |
| ECLASS-7.0 | 27440104 |
| ECLASS-8.0 | 27440104 |
| ECLASS-9.0 | 27440102 |
| ECLASS-10.1 | 27242692 |
| ECLASS-11.1 | 27242692 |
| ECLASS-12.0 | 27242692 |
| ETIM-5.0 | EC002584 |
| customs tariff number | 85366990 |
| GTIN | 4048879049825 |
| Packaging unit | 1 |
| Electrical data | |
| Terminating resistor | connectable, integrated |
| Industrial communication | |
| Data transmission rate max. | 1 MBit/s |
| Installation | |
| Connection cross section max. | 1 mm² |
| Device protection Electrical | |
| Degree of protection (EN IEC 60529) | IP20 |
| Mechanical data Mounting data | |
| Height | 65 mm |

| | |
|-------|-------|
| Width | 48 mm |
|-------|-------|

| | |
|-------|-------|
| Depth | 16 mm |
|-------|-------|

Environmental characteristics | Climatic

| | |
|----------------------------|------|
| Operating temperature min. | 0 °C |
|----------------------------|------|

| | |
|----------------------------|-------|
| Operating temperature max. | 60 °C |
|----------------------------|-------|

| | |
|--------------------------|--------|
| Storage temperature min. | -25 °C |
|--------------------------|--------|

| | |
|--------------------------|-------|
| Storage temperature max. | 80 °C |
|--------------------------|-------|

Connection type 2

| | |
|--------------------------|-------|
| Family construction form | D-Sub |
|--------------------------|-------|

| | |
|--------|--------|
| Gender | female |
|--------|--------|

| | |
|--------------|---|
| No. of poles | 9 |
|--------------|---|

| | |
|-------|-------|
| PIN 2 | CAN_L |
|-------|-------|

| | |
|-------|---------|
| PIN 3 | CAN_GND |
|-------|---------|

| | |
|-------|----------|
| PIN 5 | CAN_SHLD |
|-------|----------|

| | |
|-------|-----|
| PIN 6 | 0 V |
|-------|-----|

| | |
|-------|-------|
| PIN 7 | CAN_H |
|-------|-------|

| | |
|-------|---------|
| PIN 9 | CAN V + |
|-------|---------|

| | |
|------------|--------------------|
| Connection | Screw terminals SK |
|------------|--------------------|

| | |
|--------------------------|----------|
| Family construction form | terminal |
|--------------------------|----------|

| | |
|--------|--------|
| Gender | female |
|--------|--------|

| | |
|--------------|---|
| No. of poles | 6 |
|--------------|---|