MURR ELEKTRONIK
stay connected

## MB CAP ULTRA ADD-ON-MODULE


IN: 0-26,4VDC OUT:0-26,4VDC/3A for max.1A/21S


INPUT: 24 V DC (SELV/PELV)
OUTPUT: max. 3 A
12 s (3 A); 36 s (1 A)

[Link to Product]

### Illustration




Product may differ from Image

### Commercial data

| | |
|---|---|
| ECLASS-6.0 | 27049190 |
| ECLASS-6.1 | 27049201 |
| ECLASS-7.0 | 27049201 |
| ECLASS-8.0 | 27049201 |
| ECLASS-9.0 | 27049201 |
| ECLASS-10.1 | 27040692 |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-29

MURR ELEKTRONIK
stay connected

| | |
|---|---|
| ECLASS-11.1 | 27040692 |
| ECLASS-12.0 | 27040692 |
| ETIM-5.0 | EC002584 |
| customs tariff number | 85322900 |
| GTIN | 4048879079792 |
| Packaging unit | 1 |
| **Electrical data** | |
| Security level | SELV/PELV |
| **Electrical data \| Input** | |
| Input voltage DC min. | 0 V |
| Input voltage DC max. | 26,4 V |
| Current input AC | 3 A |
| Efficiency | 90 % |
| **Electrical data \| Output** | |
| Output voltage DC min. | 0 V |
| Output voltage DC max. | 26,4 V |
| Output voltage adjustable | yes |
| Output current max. | 3 A |
| **Mechanical data \| Mounting data** | |
| Mounting method | geschnappt |
| Suitable for mounting type | Mounting rail TH35, (EN 60715) |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 60 °C |
| Storage temperature min. | -20 °C |
| Storage temperature max. | 60 °C |
| **Conformity** | |
| Product standard | EN 60950, EN 50178 |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-29