



MET SINGLE-PHASE CONTROL AND ISOLATION TRANSFORMER

P:1000VA IN:400VAC±5% OUT:110VAC

Single-phase - Control and Isolation Transformers  
1000 VA  
Isolation class T 40/B

[Link to Product](#)

Illustration



Product may differ from Image

| Commercial data          |               |
|--------------------------|---------------|
| ECLASS-6.0               | 27031202      |
| ECLASS-7.0               | 27031202      |
| ECLASS-8.0               | 27031202      |
| ECLASS-9.0               | 27031202      |
| ETIM-5.0                 | EC002485      |
| customs tariff number    | 85043180      |
| GTIN                     | 4048879073875 |
| Packaging unit           | 1             |
| Electrical data   Supply |               |
| Power frequency          | 50 ... 60 Hz  |
| Electrical data   Input  |               |

|                                                 |                                               |
|-------------------------------------------------|-----------------------------------------------|
| Input voltage AC                                | 400 V                                         |
| Input voltage AC min.                           | 380 V                                         |
| Input voltage AC max.                           | 420 V                                         |
| Current input AC                                | 2,67 A                                        |
| Max. inrush current                             | 50 A                                          |
| Short-circuit current                           | 92 A                                          |
| <b>Electrical data   Output</b>                 |                                               |
| Output voltage AC 1                             | 110 V                                         |
| Output voltage adjustable                       | no                                            |
| Power rating AC max.                            | 1000 VA                                       |
| <b>Device protection   Electrical</b>           |                                               |
| Insulation test voltage input - output          | 5,8 kV                                        |
| <b>Mechanical data   Mounting data</b>          |                                               |
| Mounting method                                 | screwed                                       |
| Mounting dimension a                            | 111,5 mm                                      |
| Mounting dimension b                            | 135 mm                                        |
| Mounting dimension c                            | 7 mm                                          |
| Height                                          | 140 mm                                        |
| Width                                           | 174 mm                                        |
| Depth                                           | 163 mm                                        |
| Diameter bore                                   | 7 mm                                          |
| Length bore                                     | 11 mm                                         |
| <b>Environmental characteristics   Climatic</b> |                                               |
| Operating temperature min.                      | -20 °C                                        |
| Operating temperature max.                      | 60 °C                                         |
| Storage temperature min.                        | -20 °C                                        |
| Storage temperature max.                        | 80 °C                                         |
| <b>Conformity</b>                               |                                               |
| Product standard                                | EN 61558-1, EN 61558-2-4, EN 62041 category 0 |