

Modlight50 Pro connecting modul tube mounting

Input 24VDC

Basic for tube mounting
Connection cables are in the online shop under "Connection Technology".

Link to Product

Illustration



Product may differ from Image



Commercial data

ECLASS-6.0	27371232
ECLASS-6.1	27371232
ECLASS-7.0	27371232
ECLASS-8.0	27371232
ECLASS-9.0	27371232
ECLASS-10.1	27371232
ECLASS-11.1	27371232
ECLASS-12.0	27371232
ETIM-5.0	EC001152
ETIM-6.0	EC001152
ETIM-7.0	EC001152
customs tariff number	85319000
GTIN	4048879751513
Packaging unit	1

Electrical data | Supply

Operating voltage DC	24 V
Operating voltage DC min.	21,6 V
Operating voltage DC max.	26,4 V

Device protection | Electrical

Degree of protection (EN IEC 60529)	IP65
Additional condition protection degree	inserted, locked

Mechanical data | Material data

Color housing	black
---------------	-------

Material housing	Plastic
------------------	---------

Mechanical data | Mounting data

Height	180 mm
--------	--------

Width	50 mm
-------	-------

Depth	50 mm
-------	-------

Environmental characteristics | Climatic

Operating temperature min.	-30 °C
----------------------------	--------

Operating temperature max.	60 °C
----------------------------	-------

Connection type 1

Connection	Spring clamp terminals FK
------------	---------------------------

Family construction form	terminal
--------------------------	----------

Gender	female
--------	--------

No. of poles	9
--------------	---

PIN 1	LED-Modul RD
-------	--------------

PIN 2	LED-Modul YE
-------	--------------

PIN 3	LED-Modul GN
-------	--------------

PIN 4	LED-Modul BU
-------	--------------

PIN 5	LED-Modul CL
-------	--------------

PIN 6	Buzzer
-------	--------

PIN 7	24 V DC (0 V)
-------	---------------

PIN 8	Blinking
-------	----------

PIN 9	0 V (24 V DC)
-------	---------------