

**Modlight70 Pro LED modul amber**

Input 24VDC

LED module (yellow)

[Link to Product](#)

Illustration



Product may differ from Image



| Commercial data                        |                  |
|----------------------------------------|------------------|
| ECLASS-6.0                             | 27371200         |
| ECLASS-6.1                             | 27371220         |
| ECLASS-7.0                             | 27371220         |
| ECLASS-8.0                             | 27371220         |
| ECLASS-9.0                             | 27371220         |
| ECLASS-10.1                            | 27371220         |
| ECLASS-11.1                            | 27371220         |
| ECLASS-12.0                            | 27371220         |
| ETIM-5.0                               | EC000232         |
| customs tariff number                  | 85319000         |
| GTIN                                   | 4048879752633    |
| Packaging unit                         | 1                |
| Electrical data   Supply               |                  |
| Operating voltage DC                   | 24 V             |
| Current consumption max.               | 62,5 mA          |
| Device protection   Electrical         |                  |
| Degree of protection (EN IEC 60529)    | IP65             |
| Additional condition protection degree | inserted, locked |
| Mechanical data   Material data        |                  |
| Material housing                       | PC               |
| Mechanical data   Mounting data        |                  |
| Height                                 | 49 mm            |

|       |       |
|-------|-------|
| Width | 70 mm |
|-------|-------|

|       |       |
|-------|-------|
| Depth | 70 mm |
|-------|-------|

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -30 °C |
|----------------------------|--------|

|                            |       |
|----------------------------|-------|
| Operating temperature max. | 60 °C |
|----------------------------|-------|

**Connection type 1**

|                 |                 |
|-----------------|-----------------|
| Mounting method | bayonet-locking |
|-----------------|-----------------|