

MODL.VARIO Accessories closure plug 6/4

for adaptive inserts, nickel plated brass

Modlink Vario Accessories Locking plug Diameter 6 mm

Quantity: 10 pcs.

good resistance to oil, gasoline and chemicals

The resistance to aggressive media should be individually tested for your application. Further details on request.

Link to Product

Illustration



Product may differ from Image

Commercial data	
ECLASS-6.0	27260702
ECLASS-6.1	27269202
ECLASS-7.0	27449203
ECLASS-8.0	27449203
ECLASS-9.0	27440192
ECLASS-10.1	27440192
ECLASS-11.1	27440192
ECLASS-12.0	27440192
ETIM-5.0	EC002641
customs tariff number	85389099
GTIN	4048879618885
Packaging unit	10
Mechanical data	
Operating pressure min.	-0,8 bar
Operating pressure min. Operating pressure max.	-0,8 bar 16 bar
Operating pressure max.	
Operating pressure max. Mechanical data Material data	16 bar
Operating pressure max. Mechanical data Material data Coating housing	16 bar nickel plated
Operating pressure max. Mechanical data Material data Coating housing Material housing	16 bar nickel plated

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-04-26



Width	8 mm	
Depth	8 mm	
Environmental characteristics Clin	natic	
Operating temperature min.	-20 °C	
Operating temperature max.	120 °C	